

# BETON TROWEL

CONCRETE FINISHING  
& COMPACTION



## CONCRETE VIBRATOR HUMDINGER

Humdinger electric hand held flex drive concrete vibrators.

- Powerful lightweight power unit with robust motor protection
- Flexible shafts from 1m to 6m
- Head diameters from 25mm to 58mm
- Double insulated 2,3 kW motors, 115V & 230V



### SPECIFICATIONS:

| Model  |                               | Voltage | kW  | Hz    | Motor Speed | Weight |
|--------|-------------------------------|---------|-----|-------|-------------|--------|
| HVU110 | Humdinger Electric Power Unit | 115V    | 2,3 | 50/60 | 18.000      | 5,5    |
| HVU220 | Humdinger Electric Power Unit | 230V    | 2,3 | 50/60 | 18.000      | 5,5    |

| Model   | Vib diam | Length | Weight  | Frequency | Amplitude |
|---------|----------|--------|---------|-----------|-----------|
| HDV25/2 | 25mm     | 2m     | 5,50Kg  | 13.700    | 1,12      |
| HDV25/6 | 25mm     | 6m     | 8,50Kg  | 13.700    | 1,12      |
| HDV28/6 | 28mm     | 6m     | 9,40Kg  | 16.800    | 1,20      |
| HDV38/1 | 38mm     | 1m     | 4,96Kg  | 16.200    | 1,54      |
| HDV38/2 | 38mm     | 2m     | 6,26Kg  | 16.200    | 1,54      |
| HDV38/3 | 38mm     | 3m     | 7,56Kg  | 16.200    | 1,54      |
| HDV38/4 | 38mm     | 4m     | 8,86Kg  | 16.200    | 1,54      |
| HDV38/5 | 38mm     | 5m     | 10,36Kg | 16.200    | 1,54      |
| HDV38/6 | 38mm     | 6m     | 11,86Kg | 16.200    | 1,54      |
| HDV48/3 | 38mm     | 3m     | 8,90Kg  | 15.600    | 1,54      |
| HDV48/4 | 48mm     | 4m     | 10,20Kg | 15.600    | 1,65      |
| HDV48/5 | 48mm     | 5m     | 11,70Kg | 15.600    | 1,65      |
| HDV58/5 | 58mm     | 5m     | 12,50Kg | 15.000    | 1,68      |

